

Surge (Impulse) Current Simulator (15 kA)

S10C1500

Datasheet



In Compliance with

- > IEC 61643-1
- > GB/T 17626.5
- > GB/T16927.1
- > GB/T 16896.1
- > GB11032-2000
- > GB18802.1-2002
- > YD/T 1235.2-2002
- > UL1449

Introduction

S10C series surge (impulse) current simulator is based on 3ctest third-generation intelligent multiple function comprehensive test simulator. One stop multi-waveform surge test platform is built by combination of different waveform generation network. Programmable controller and computer technology is applied for control. Unique color touch screen and friendly human-machine interface. It highly enhances test efficiency for high voltage and current test with easy operation. Setting simple test requirements on parameters setting page, all test can be done automatically. It is featured with high system integration and intelligence, easy operation and safety system to save time and space.

Features

- > Color touch screen 7 inch LCD
- > PLC control system, automatic control system
- > Current and voltage LCD display
- > One-button test with programmable function
- > RS232 communication port for remote control
- > Internal ground device and safety lock

Application Areas

- | | |
|-----------------|--------------|
| > Communication | > Technology |
| > Telecom | > Military |
| > Medical | > Avionics |
| > Broadcast | > New energy |
| > Railway | |

Technical Parameters	
Model	S10C1500
Output waveform	8/20 μ s ($\pm 10\%$) current wave
Output peak current	15 kA $\pm 10\%$ Reversed polarity peak <20%
Voltage polarity	+/- (automatic switch)
Charging time	10 s ~ 999 s
Charging voltage instability	Less than 1%
Trigger mode	Automatic or manual, single trigger
Trigger malfunction	Less than 1%
Trigger range	100% rated charging voltage
Measurement display resolution	Better than 3%
Insulation strength	≤ 500 V RMS (common port COMMON to reference ground PE)
Auxiliary mains voltage	220 V ($\pm 10\%$)/50 Hz
Auxiliary mains current	<10 A (continuous)

General Parameters	
Power supply	AC 220 V $\pm 10\%$, 50/60 Hz
Temperature	-10 °C ~ +40 °C
Humidity	35% ~ 85% RH (no condensation)
Ground resistance	No more than 0.5 Ω
Dimension	600x800x1171 mm (22U)
Weight	Approx. 200 kg
No conductive dust, no fire or explosion danger, no corrosive metal and insulation air. Waveform of mains voltage is sine wave. The THD is <5%.	

Optional accessories for S10 series simulator:			
Name	Model	Installation (connection) mode	Reference picture
Oscilloscope	MDO3012	External	
Current probe	CM 0220M	Internal	
Voltage probe	P6015 A, 40 kV Peak	External	
Peak acquisition system	Internal acquisition system for voltage and current, touch screen display	Internal	
Test box	PA 350	External	
Remote control software	MAS3000, programmable test from PC port, support Win xp, Win7	RS232	



MAINLAND CHINA

SUZHOU 3CTEST ELECTRONIC CO., LTD.

Add.: No. 99 Emeishan Rd, SND, Suzhou 215153,

Tel: +86 (0)512 6807 7192

Fax: +86-512-68079795

Email: globalsales@3ctest.cn

www.3c-test.com

TAIWAN

RICHTEC INSTRUMENTS CO., LTD.

Add.: 6F.-5, No.130, Ln. 235, Baoqiao Rd., Xindian

Dist., New Taipei City 23145, Taiwan, China

Tel: +886 2 8912 1185 #10

Email: ryan@richtec.com.tw

www.richtec.com.tw

SOUTH KOREA

TESTEK Co., LTD.

Add.: 601Ho, SungwoonKoa, 141 Hyeonam-ro,

Suji-Gu, Yongin-Si, Gyeonggi-Do, South Korea.

Tel: +82 70 4099 2071,

E-mail: woo@testek.co.kr

www.testek.co.kr

SINGAPORE

QUANTEL PTE LTD.

Add.: 25 Kallang Ave, #05-02, 339416, Singapore

Tel: +65 6745 3200

Email: engtat.ong@sg.quantel-global.com

www.quantel-global.com

USA

THE EMC SHOP

Add.: 7401 Galilee Rd. #160, Roseville, CA 95678,

USA

Tel: +1 844 423 7435

Email: brendon.berg@theemcshop.com

www.theemcshop.com

RUSSIA

CDIP LLC

Add.: Room 7, Building 5, House 69, Ryabinovaya

Street, Moscow 121471, Russia

Tel: +7 (495) 956 20 22

Email: info@cdip.ru

www.cdip.ru